



# Emergency Drench Showers







### **ABOUT US**

Incorporated in 1990, METHOD began as a trading entity primarily focusing on supplying imported laboratory service fittings to the local market.

The growing laboratory market seeking a more cost-effective option became the reason METHOD pioneered the manufacturing of laboratory fittings in Malaysia in 1994. Starting out from a humble workshop, we focused on providing an affordable yet quality alternative to the market. With the support from our customers, we quickly expanded into a reputable one-stop laboratory fixture supplier.

We manufacture and supply emergency shower & eyewash, laboratory fittings, laboratory sinks, fume extraction system, laboratory storage cabinet & spill containment and laboratory worktops.

Today, METHOD laboratory and safety products are used and trusted in over 40 countries worldwide. Our commitment to providing uncompromising quality and affordable solutions to our customers remain to this day and beyond.















### **CERTIFICATES**









Do and Dont's	1
Installation Procedures	2
Maintenance and Warranty	3
Performance and Assurance of New Eyewash	4
Wall Mounted Eyewash	5
Floor Mounted Eyewash	12
Bench Mounted Eyewash	13
Handheld Spray Unit	15
Vertically Mounted Drench Shower	16
Horizontally Mounted Drench Shower	18
Floor Mounted Drench Shower	20
Floor Mounted Combination Unit	22
Full Stainless Steel Floor Mounted Combination Unit	32
Decontamination Shower in Stainless Steel	34
Portable Eyewash Station	35
Stainless Steel Platform with Sum and Removable Cover	37
Barrier Free FRP Shower Booth	38
Portable Emergency Shower Tank Tester	39
Parts and Accessories	40
PLUM Eyewash	42
PLUM Quickfix	46



### DO AND DONT'S ABOUT EMERGENCY EQUIPMENT

METHOD produces a high quality range of Emergency Eyewashes & Drench Showers for the chemical-related industries, laboratories, hospitals, schools, colleges and universities.

In line with the OSHA Rules and Regulations, every effort must be made to save sight and skin and alleviate suffering at workplaces in the event of an accident.

### Do's

Ensure that the equipment is used for the purpose for which it is intended for. It only serves to supplement first-aid treatment.

Ensure that all employees know the purpose of the emergency equipment. Employees exposed to or working in hazardous areas must be aware of the locations of the equipment and properly trained on the use of the equipment.

Install the emergency equipment as close as eyewash and drench shower fixtures. The path to the equipments should be free from obstructions.

Ensure that a sufficient supply of water is readily available for the equipment at all times.

Ensure that the piping should not be smaller than the inlet of the equipment and has a minimum of 30psi (2 bar) of flow pressure. The ideal flow pressure at all times should be between 30 to 45psi (2 to 3 bar).

Install emergency eyewash and shower equipment that meet the standards from American National Standards Institute (ANSI Z358.1).

### Dont's

Do not discontinue the use of protective devices like eye and face protectors and protective clothing. The installation of emergency equipment should not be seen as a substitute for these protective devices.

Do not use the eye/face wash units if it is known that the eye injury is due to metal or some other solid fragments. Medical attention and help must be sought immediately.

Do not alter the dimensions or heights of the equipment as recommended in this catalogue as the standards comply to ANSI Z358.1 requirements.

Do not depend on sink faucets as a replacement of emergency shower or eyewash.



### **INSTALLATION PROCEDURES**

- 1 Install unit as close as possible to the hazardous areas.
- 2 Emergency equipment should be installed in an accessible location that requires about 10 seconds to reach and should be within a travel distance estimated of 30.5 meters (100 feet) from the hazardous area.
- 3 Emergency equipment should be connected to the main potable water supply having a minimum flow pressure of 30psi (2 Bar) and a maximum of 80psi (5.5 Bar). Any flow pressure lower than 30psi (2 Bar) will not give the desired flow rate, which may result in non-compliance.
- 4 Do not use a smaller pipe size than inlet size of the unit. For eyewash units, pipe size should be bigger than 1/2" Iron Pipe Size (IPS). For shower units, pipe size should be no less than 1" IPS.
- 5 As per ANSI requirement, discharge water from the equipment should be in an appropriate temperature range of 16°C to 38°C (60°F to 100°F).
- 6 In circumstances where the chemical reaction is acclerated by water temperature, a medical advisor should be consulted for the optimum temperature for each application.
- 7 If shut-off valve should be installed for maintenance purpose, it is recommended that the shut-off valve is be under lock and keys, as to prevent unwanted closing of the valve.
- 8 Emergency equipment that are installed in remote areas of the workplace or in hazardous locations, an audible alarm system should be installed. This will alert the surrounding personnel as the equipment are being used.
- **9** Whenever possible, a filter should be provided upstream of the eyewash to remove particles from the water and prevent additional eye injury.
- 10 Installation procedures should be in accordance with proper plumbing practices and supply sized adequately to meet flow requirements.
- 11 Install the emergency equipment away from energised electrical equipment.



### **MAINTENANCE & WARRANTY**

### Maintenance

- All emergency drench shower and eyewash should be properly maintained and tested weekly. After the testing process, the tester has to record the data and initial on the test tag which is attached near to the unit.
- If there is no floor drain available, a dry shower test kit can be used.
- If a shut-off valve is installed for maintenance purposes, please ensure that it is turned on after maintenance.

### Warranty

Method warrants that all of its products are guaranteed against defects in material and poor workmanship under normal use and service upon the following terms and conditions:

- That we will replace free of charge after inspection, any parts found to be defective within 12 months from the date of our invoice at our option, F.O.B. Kuala Lumpur, Malaysia. Method will not be liable for equipments damaged by accident, abuse, improper installation, or improper maintenance.
- That the repair, alterations or replacement or for any expense connected herewith made by the user, buyer or buyer's agents shall not be liability of Method. Method will not be liable for any installation, dismantling or any other labour charges incurred in this instance.
- That Method has made no other warranties either expressed or implied in addition to those stated here-in, except that of title with respect to any of the products or equipment sold hereunder and that Method shall not be liable for general, special or consequential damages claimed to arise under the contract of sale.
- That owing to widely varying conditions, Method cannot guarantee that the use of this emergency equipment will prevent serious injury or in alleviation of existing or prior injuries.



### PERFORMANCE AND ASSURANCE OF NEW EYEWASH (IM-55-AV1X)

### **CONVENTIONAL EYEWASH**



Occasional unbalanced water stream



Unchecked pressure leads to messy and wet surroundings



Requires supply pressure of 2 bar or more



Parts can be easily tampered or removed

### **IM-55-AV1X**



Consistently achieve perfect stream



Manually regulate flow to ensure steady stream regardless of pressure



Performs well at approximately 1 bar




Uniquely designed to reduce risk of tampering


 $<sup>^{*}\</sup>text{IM-55-AV1X}$  eyewash is suitable with previous Method eyewash and shower model.




### WALL MOUNTED EYEWASH WITH ABS PLASTIC BOWL









MOUNT DETAILS

### **MODEL: EY 5050 AB**

Where space may be of constraint, METHOD wall-mounted eyewash fits easily into your workplace. Eyewash works quickly with a simple push of its highly visible handle. METHOD eyewash sprayheads use soft-flow aerators and automatic pressure compensating valve.


Model	EY 5050 AB
Bowl Size	280mm
Bowl Material	ABS Plastic Bowl
Colour	Traffic Yellow
Connecting Fittings	Stainless Steel 304 (Schedule 40)
Connection Type	BSP
Outlet Size	1 ¼"
Inlet Size	1/2"
Flow Rate	At least 15 litres/ minute
Control Valve	Stainless Steel 316
Operating Pressure	2 Bar
Signage	Eyewash
Certification	ANSI Z358.1 & AS 4775
Options	Foot pedal assembly for user to operate without using hand. Please ask for Model EY 5070AB


### \*Pipe Threads




### WALL MOUNTED EYEWASH WITH STAINLESS STEEL BOWL









### MODEL: EY 5050 SS

Where space may be of constraint, METHOD wall-mounted eyewash fits easily into your workplace. Eyewash works quickly with a simple push of its highly visible handle. METHOD eyewash sprayheads use soft-flow aerators and automatic pressure compensating valve.


Model	EY 5050 SS
Bowl Size	280mm
Bowl Material	Stainless Steel Bowl
Colour	Traffic Yellow
Connecting Fittings	Stainless Steel 304 (Schedule 40)
Connection Type	BSP
Outlet Size	1 1/4"
Inlet Size	1/2"
Flow Rate	At least 15 litres/ minute
Control Valve	Stainless Steel 316
Operating Pressure	2 Bar
Signage	Eyewash
Certification	ANSI Z358.1 & AS 4775
Options	Foot pedal assembly for user to operate without using hand. Please ask for Model EY 5070SS


### \*Pipe Threads




### BENCH MOUNTED EYEWASH WITH ABS PLASTIC BOWL









### **MODEL: EY 5059 AB**

This bench mounted eyewash with ABS plastic bowl can fit easily to any workplace and laboratory. This eyewash works quickly with a simple push of its highly visible handle. Our eyewash spray heads use the soft-flow aerators and automatic pressure compensating valve inbuilt in the spray head assembly.


Model	EY 5059 AB
Bowl Size	280mm
Bowl Material	ABS Plastic Bowl
Colour	Traffic Yellow
Connecting Fittings	Stainless Steel 304 (Schedule 40)
Connection Type	BSP
Outlet Size	1"
Inlet Size	1/2"
Flow Rate	At least 15 litres/ minute
Control Valve	Stainless Steel 316
Operating Pressure	2 Bar
Signage	Eyewash
Certification	ANSI Z358.1 & AS 4775


### \*Pipe Threads




### BENCH MOUNTED EYEWASH WITH STAINLESS STEEL BOWL









### **MODEL: EY 5059 SS**

This bench mounted eyewash with Stainless Steel bowl can fit easily to any workplace and laboratory. This eyewash works quickly with a simple push of its highly visible handle. Our eyewash spray heads use the soft-flow aerators and automatic pressure compensating valve inbuilt in the spray head assembly.

EY 5059 SS
280mm
Stainless Steel Bowl
Traffic Yellow
Stainless Steel 304 (Schedule 40)
BSP
1"
1/2"
At least 15 litres/ minute
Stainless Steel 316
2 Bar
Eyewash
ANSI Z358.1 & AS 4775


### \*Pipe Threads






### FLOOR MOUNTED EYEWASH WITH ABS PLASTIC BOWL







# MODEL: EY 5060 AB | EY 5070 AB MODEL: GIY 5060 AB | GIY 5070 AB

This stand alone eyewash is mounted onto the floor and can operated either by hand or foot. METHOD eyewash sprayheads use soft-flow aerators and automatic pressure compensating valve.


Model	EY 5060 AB	EY 5070 AB	
Bowl Size	280mm		
Bowl Material	ABS Plastic Bowl		
Colour	Traffic Yellow		
Connecting Fittings	Stainless Steel 304 (Schedule 40)		
Connection Type	BSP		
Outlet Size	1"		
Inlet Size	1/2"		
Flow Rate	At least 15 litres/ minute		
Control Valve	Stainless Steel 316		
Operating Pressure	2 Bar		
Signage	Eyewash		
Certification	ANSI Z358.	1 & AS 4775	
Options	fittings, please requ	assembly with 6 feet Model EY 5010AB nbly, please ask for	


### \*Pipe Threads



### FLOOR MOUNTED EYEWASH WITH STAINLESS STEEL BOWL







### MODEL: EY 5060 SS | EY 5070 SS MODEL: GIY 5060 SS | GIY 5070 SS

These units work very well in any environment. It can be mounted onto a floor and operated either by hand or by foot. METHOD eyewash sprayheads use soft-flow aerators and automatic pressure compensating valve.


Model	EY 5060 SS	EY 5070 SS
Bowl Size	280mm	
Bowl Material	Stainless Steel Bowl	
Colour	Traffic Yellow	
Connecting Fittings	Stainless Steel 304 (Schedule 40)	
Connection Type	BSP	
Outlet Size	1"	
Inlet Size	1/2"	
Flow Rate	At least 15 litres/ minute	
Control Valve	Stainless Steel 316	
Operating Pressure	2 Bar	
Signage	Eyewash	
Certification	ANSI Z358.1 & AS 4775	
Options	fittings, please requ	assembly with 6 feet Model EY 5010SS nbly, please ask for


### \*Pipe Threads



### FLOOR MOUNTED EYEWASH WITH NATURAL STAINLESS STEEL FINISH







### MODEL: EPX 5060 AB | EPX 5070 AB

This stand alone eyewash is mounted onto the floor and can operated either by hand or foot. METHOD eyewash sprayheads use soft-flow aerators and automatic pressure compensating valve.


EPX 5060 AB	EPX 5070 AB
280mm	
ABS Plastic Bowl	
Natural Finish	
Stainless Steel 304	
BSP	
1"	
1/2"	
At least 15 litres/ minute	
Stainless	Steel 316
2 E	3ar
Eyev	vash
ANSI Z358.	I & AS 4775
	280 ABS Plas Natural Stainless BS 1


### \*Pipe Threads



### FLOOR MOUNTED EYEWASH WITH NATURAL STAINLESS STEEL FINISH







### MODEL: EPX 5060 SS | EPX 5070 SS

These units work very well in any environment. It can be mounted onto a floor and operated either by hand or by foot. METHOD eyewash sprayheads use soft-flow aerators and automatic pressure compensating valve.


EPX 5060 SS	EPX 5070 SS
280mm	
Stainless Steel 304	
Natural Finish	
Stainless Steel 304	
BSP	
1"	
1/2"	
At least 15 litres/ minute	
Stainless	Steel 316
2 [	3ar
Eyev	vash
ANSI Z358.	1 & AS 4775
	280 Stainless Natura Stainless B: 1/ At least 15 li Stainless 2 E


### \*Pipe Threads



### FLOOR MOUNTED EYEWASH WITH NATURAL STAINLESS STEEL FINISH







### MODEL: EY 5060 XSS | EY 5070 XSS

These units work very well in any environment. It can be mounted onto a floor and operated either by hand or by foot. METHOD eyewash sprayheads use soft-flow aerators and automatic pressure compensating valve.

Model	EX 5060 XSS	EY 5070 XSS
Bowl Size	280mm	
Bowl Material	Stainless Steel Bowl	
Colour	Natural Finish	
Stanchion	Stainless Steel 304	
Connecting Fittings	Stainless Steel 304	
Foot Pedal	Not available	Stainless Steel 304
Pedestal	Stainless Steel 304	
Connection Type	BSP	
Outlet Size	1"	
Inlet Size	1/2"	
Flow Rate	At least 15 litres/ minute	
Control Valve	Stainless Steel 316	
Operating Pressure	2 Bar	
Signage	Eyewash	
Certification	ANSI Z358.1 & AS 4775	

### \*Pipe Threads



### BENCH FLUSHED BOWL EYEWASH WITH PRESS DOWN HANDLE

### COUNTER TOP MOUNTED SWIVEL EYEWASH



**EXX 3030 SS** 


### MODEL: EXX 3030 SS | EXG 313

This neat looking eyewash is designed for laboratory benches. The push-down plunger activates the eyewash to give a good steady soft-flow of water. It also incorporates our standard automatic compensating valve in the sprayheads assembly.


EXG 313	

	<b>A</b>	
ľ		

Model	EXX 3030 SS	EXG 313
Bowl Size	280mm	N/A
Bowl Material	Stainless Steel 304 (Schedule 40)	
Colour	Traffic Yellow	
Connecting Fittings	Stainless Steel 304 (Schedule 40)	
Connection Type	BSP	
Inlet Size	1/2"	
Flow Rate	At least 15 litres/ minute	
Control Valve	Stainless Steel 316	
Recommended Working Pressure	re 2 Bar	
Signage	Eyewash	
Certification	ANSI Z358.1 & AS 4775	



### \*Pipe Threads





### HANDHELD SPRAY UNIT





### MODEL: E 700-10 SS | E 700-20 SS | E 700-30 SS


A simple handheld spray unit designed for emergency cleansing of eyes and face. Handle stays open when squeezed.

Model	E 700-10 SS	E 700-20 SS	E 700-30 SS
Category	Bench Mounted		
Drench Hose	1500 mm		
Hose Type	Stainless Steel		
Water Supply	1/2" IPS		
Signage	Eyewash		
Compliance	ANSI Z358.1 & AS 4775		
Hole Diameter for Mounting Base	35 mm ø		



### VERTICALLY MOUNTED DRENCH SHOWER WITH ABS PLASTIC BOWL





### MODEL: EQ 9910V AB

This simple to operate overhead drench shower may just be what you are looking for. A durable and affodable choice, it is a must have in hazardous work surroundings.


Model	EQ 9910V AB
Bowl Size	280mm
Bowl Material	ABS Plastic Bowl
Colour	Traffic Yellow
Connecting Fittings	Stainless Steel 304 (Schedule 40)
Connection Type	BSP
Outlet Size	1"
Flow Rate	At least 90 litres/ minute
Control Valve	Stainless Steel 316
Operating Pressure	2 Bar
Signage	Drench Shower
Certification	ANSI Z358.1 & AS 4775

### \*Pipe Threads



### VERTICALLY MOUNTED DRENCH SHOWER WITH STAINLESS STEEL BOWL





### MODEL: EQ 9910V SS

This vertical shower effectively drenches the body with large quantity of water. Its durable stainless steel bowl gives you long lasting service.

### \*Pipe Threads




EQ 9009V SS



### HORIZONTALLY MOUNTED DRENCH SHOWER WITH ABS PLASTIC BOWL





### MODEL: EQ 9930H AB

This horizontal wall supply unit gives an outstanding performance like any other drench showers. Easy to operate with fast-action valve, it is a must for hazardous. environtment.


EQ 9930H AB
280mm
ABS Plastic Bowl
Traffic Yellow
Stainless Steel 304 (Schedule 40)
BSP
1"
At least 90 litres/ minute
Stainless Steel 316
2 Bar
Drench Shower
ANSI Z358.1 & AS 4775

### \*Pipe Threads



### HORIZONTALLY MOUNTED DRENCH SHOWER WITH STAINLESS STEEL BOWL





### MODEL: EQ 9930H SS

Designed for wall incoming water supply, this drench shower will serve you efficiently for many years. Fast-action valve with pull-down operation.


Model	EQ 9930H SS
Bowl Size	280mm
Bowl Material	Stainless Steel Bowl
Colour	Traffic Yellow
Connecting Fittings	Stainless Steel 304 (Schedule 40)
Connection Type	BSP
Outlet Size	1"
Flow Rate	At least 90 litres/ minute
Control Valve	Stainless Steel 316
Operating Pressure	2 Bar
Signage	Drench Shower
Certification	ANSI Z358.1 & AS 4775

### \*Pipe Threads





# 815 (Including Pedestal) 1" IPS Supply 1" Stainless Steel / Galvanised Iron Pipe Aluminium Pedestal 250mm (10 inch)



### MODEL: EQ 9980 AB | GIQ 9980 AB

Designed for locations where wall or ceiling units are not permissible. Mounted onto the floor, this unit is for any hazardous areas.

EQ 9980 AB	GIQ 9980 AB
Stainless Steel 304 (Schedule 40)	Galvanised Iron
Stainless Steel 304 (Schedule 40)	Galvanised Iron
280mm	
ABS Plastic Bowl	
Traffic Yellow	
BSP	
1"	
At least 90 litres/ minute	
Stainless Steel 316	
2 Bar	
Drench Shower	
ANSI Z358.1 & AS 4775	
	Stainless Steel 304 (Schedule 40)  Stainless Steel 304 (Schedule 40)  280r  ABS Plass  Traffic Y  BS  1"  At least 90 lit  Stainless  2 B  Drench S

### \*Pipe Threads







# 815 (Including Pedestal) 1" IPS Supply 1" Stainless Steel / Galvanised Iron Pipe Aluminium Pedestal 250mm (10 inch)



### MODEL: EQ 9980 SS | GIQ 9980 SS


Designed for locations where wall and ceiling units are not permissible. Bolted onto the floor, this unit will give years of trouble free service. The stainless steel bowl makes it an ideal unit for outdoor placement.


EQ 9980 SS	GIQ 9980 SS
Stainless Steel 304 (Schedule 40)	Galvanised Iron
Stainless Steel 304 (Schedule 40)	Galvanised Iron
280mm	
Stainless Steel Bowl	
Traffic Yellow	
BSP	
1"	
At least 90 litres/ minute	
Stainless Steel 316	
2 Bar	
Drench Shower	
ANSI Z358.1 & AS 4775	
	Stainless Steel 304 (Schedule 40)  Stainless Steel 304 (Schedule 40)  280r  Stainless S  Traffic S  BS  1"  At least 90 lit  Stainless  2 B  Drench S

### \*Pipe Threads









### MODEL: ECB 10020 AB | GIC 10020 AB


Our combination unit of drench shower and eyewash is popular in workplace where fire and chemical spillages may occur. All control valves are the instant action, stay opened type of ball valve.


Model	ECB 10020 AB	GIC 10020 AB
Stanchion	Stainless Steel 304 (Schedule 40)	Galvanised Iron
Connecting Fittings	Stainless Steel 304 (Schedule 40)	Galvanised Iron
Bowl Size	280mm	
Bowl Material	ABS Plastic Bowl	
Colour	Traffic Yellow	
Connection Type	BSP	
Outlet Size	1"	
Inlet Size	1"	
Flow Rate	At least 90 litres/ minute	
Control Valve	Stainless Steel 316	
Operating Pressure	2 Bar	
Signage	Drench Shower and Eyewash	
Certification	ANSI Z358.1 & AS 4775	

### \*Pipe Threads









### MODEL: ECB 10020 SS | GIC 10020 SS

The most popular combination unit of drench shower and eyewash for any industries, this unit is effective and highly recommended in all accident prone areas.


ECB 10020 SS	GIC 10020 SS
Stainless Steel 304 (Schedule 40)	Galvanised Iron
Stainless Steel 304 (Schedule 40)	Galvanised Iron
280mm	
Stainless Steel Bowl	
Traffic Yellow	
BSP	
1"	
At least 90 litres/ minute	
Stainless Steel 316	
2 Bar	
Drench Shower and Eyewash	
ANSI Z358.1 & AS 4775	
	Stainless Steel 304 (Schedule 40)  Stainless Steel 304 (Schedule 40)  280  Stainless S  Traffic  BS  1'  At least 90 lit  Stainless  2 B  Drench Shower


### \*Pipe Threads



# FLOOR MOUNTED COMBINATION UNIT DRENCH SHOWER AND EYEWASH WITH ABS PLASTIC BOWL COMBINE WITH FOOT PEDAL







### MODEL: ECB 10022 AB | GIC 10022 AB

Our combination unit of drench shower and eyewash is popular in workplace where fire and chemical spillages may occur. All control valves are the instant action, stay opened type of ball valve.


Model	ECB 10022 AB	GIC 10022 AB
Stanchion	Stainless Steel 304 (Schedule 40)	Galvanised Iron
Connecting Fittings	Stainless Steel 304 (Schedule 40)	Galvanised Iron
Bowl Size	280mm	
Bowl Material	ABS Plastic Bowl	
Colour	Traffic Yellow	
Connection Type	BSP	
Outlet Size	1"	
Inlet Size	1"	
Flow Rate	At least 90 litres/ minute	
Control Valve	Stainless Steel 316	
Operating Pressure	2 Bar	
Signage	Drench Shower and Eyewash	
Certification	ANSI Z358.1 & AS 4775	


### \*Pipe Threads



# FLOOR MOUNTED COMBINATION UNIT DRENCH SHOWER AND EYEWASH WITH STAINLESS STEEL BOWL COMBINE WITH FOOT PEDAL







### MODEL: ECB 10022 SS | GIC 10022 SS

Our combination unit of drench shower and eyewash is popular in workplace where fire and chemical spillages may occur. All control valves are the instant action, stay opened type of ball valve. The unit also comes with a foot pedal.


Model	ECB 10022 SS	GIC 10022 SS
Stanchion	Stainless Steel 304 (Schedule 40)	Galvanized Iron
Connecting Fittings	Stainless Steel 304 (Schedule 40)	Galvanized Iron
Bowl Size	280mm	
Bowl Material	Stainless Steel Bowl	
Colour	Traffic Yellow	
Connection Type	BSP	
Outlet Size	1"	
Inlet Size	1"	
Flow Rate	At least 90 litres/ minute	
Control Valve	Stainless Steel 316	
Operating Pressure	2 Bar	
Signage	Drench Shower and Eyewash	
Certification	ANSI Z358.1 & AS 4775	

### \*Pipe Threads



# FLOOR MOUNTED COMBINATION UNIT DRENCH SHOWER AND EYEWASH WITH ABS PLASTIC AND STAINLESS STEEL BOWL







### MODEL: ECB 10000 | GIC 10000

Our combination unit of drench shower and eyewash is popular in workplace where fire and chemical spillages may occur. All control valves are the instant action, stay opened type of ball valve.


Model	ECB 10000	GIC 10000
Stanchion	Stainless Steel 304 (Schedule 40)	Galvanised Iron
Connecting Fittings	Stainless Steel 304 (Schedule 40)	Galvanised Iron
Bowl Size	280mm	
Bowl Material	Stainless Steel Bowl	
Colour	Traffic Yellow	
Connection Type	BSP	
Outlet Size	1"	
Inlet Size	1"	
Flow Rate	At least 90 litres/ minute	
Control Valve	Stainless Steel 316	
Operating Pressure	2 Bar	
Signage	Drench Shower and Eyewash	
Certification	ANSI Z358.1 & AS 4775	


### \*Pipe Threads



# FLOOR MOUNTED COMBINATION UNIT DRENCH SHOWER AND EYEWASH OF ABS PLASTIC AND STAINLESS STEEL BOWL WITH FOOT PEDAL







### MODEL: ECB 10001 | GIC 10001

Our combination unit of drench shower and eyewash is popular in workplace where fire and chemical spillages may occur. All control valves are the instant action, stay opened type of ball valve. The unit also comes with a foot pedal.


Madal	FCD 10001	CIC 10001
Model	ECB 10001	GIC 10001
Stanchion	Stainless Steel 304 (Schedule 40)	Galvanized Iron
Connecting Fittings	Stainless Steel 304 (Schedule 40)	Galvanized Iron
Bowl Size	280mm	
Bowl Material	Stainless Steel Bowl	
Colour	Traffic Yellow	
Connection Type	BSP	
Outlet Size	1"	
Inlet Size	1"	
Flow Rate	At least 90 litres/ minute	
Control Valve	Stainless Steel 316	
Operating Pressure	2 Bar	
Signage	Drench Shower and Eyewash	
Certification	ANSI Z358.1 & AS 4775	


### \*Pipe Threads



# COMBINATION UNIT OF DRENCH SHOWER AND EYEWASH WITH NATURAL STAINLESS STEEL FINISH







### MODEL: EPX 10020 AB

This model is natural stainless steel finish for areas which prefer a safety shower eyewash that blends in with the surround aesthethics.


Model	EPX 10020 AB
Stanchion	Stainless Steel 304
Connecting Fittings	Stainless Steel 304
Pedestal	Aluminium
Bowl Size	280mm
Bowl Material	Stainless Steel 304
Colour	Natural Finish
Connection Type	BSP
Outlet Size	1"
Inlet Size	1"
Flow Rate	At least 90 litres/ minute
Control Valve	Stainless Steel 316
Operating Pressure	2 Bar
Signage	Drench Shower and Eyewash
Certification	ANSI Z358.1 & AS 4775


### \*Pipe Threads



# COMBINATION UNIT OF DRENCH SHOWER AND EYEWASH WITH NATURAL STAINLESS STEEL FINISH







### **MODEL: EPX 10022 AB**

This model is natural stainless steel finish for areas which prefer a safety shower eyewash that blends in with the surround aesthethics.


Model	EPX 10022 AB
Stanchion	Stainless Steel 304
Connecting Fittings	Stainless Steel 304
Pedestal	Aluminium
Bowl Size	280mm
Bowl Material	Stainless Steel 304
Colour	Natural Finish
Connection Type	BSP
Outlet Size	1"
Inlet Size	1"
Flow Rate	At least 90 litres/ minute
Control Valve	Stainless Steel 316
Operating Pressure	2 Bar
Signage	Drench Shower and Eyewash
Certification	ANSI Z358.1 & AS 4775


### \*Pipe Threads



# COMBINATION UNIT OF DRENCH SHOWER AND EYEWASH WITH NATURAL STAINLESS STEEL FINISH







### MODEL: EPX 10020 SS

This model is natural stainless steel finish for areas which prefer a safety shower eyewash that blends in with the surround aesthethics.


EPX 10020 SS
Stainless Steel 304
Stainless Steel 304
Aluminium
280mm
Stainless Steel 304
Natural Finish
BSP
1"
1"
At least 90 litres/ minute
Stainless Steel 316
2 Bar
Drench Shower and Eyewash
ANSI Z358.1 & AS 4775


### \*Pipe Threads



# COMBINATION UNIT OF DRENCH SHOWER AND EYEWASH WITH FOOT PEDAL IN NATURAL STAINLESS STEEL FINISH







### MODEL: EPX 10022 SS


This model is natural stainless steel finish for areas which prefer a safety shower eyewash that blends in with the surround aesthethics.

Model	EPX 10022 SS
Stanchion	Stainless Steel 304
Connecting Fittings	Stainless Steel 304
Foot Pedal	Aluminium
Pedestal	Aluminium
Bowl Size	280mm
Bowl Material	Stainless Steel 304
Colour	Natural Finish
Connection Type	BSP
Outlet Size	1"
Inlet Size	1"
Flow Rate	At least 90 litres/ minute
Control Valve	Stainless Steel 316
Operating Pressure	2 Bar
Signage	Drench Shower and Eyewash
Certification	ANSI Z358.1 & AS 4775
	·

### \*Pipe Threads









### MODEL: ECB 10020 XSS | QCB 10020 XSS

This model is designed for cleanroom and areas where airborne particles is a concern. A non-coated fixture, it is the most durable unit of the emergency fixtures range.


Model	ECB 10020 XSS	QCB 10020 XSS
Stanchion	Stainless Steel 304 (Schedule 40)	Stainless Steel 316
Connecting Fittings	Stainless Steel 304 (Schedule 40)	Stainless Steel 316
Bowl Size	280mm	
Bowl Material	Stainless Steel 304 (Schedule 40)	
Colour	Silver gray	
Connection Type	BSP	
Outlet Size	1"	
Inlet Size	1"	
Shower Flow Rate	At least 90 litres/ minute	
Eyewash Flow Rate	At least 15 litres/ minute	
Control Valve	Stainless Steel 316	
Operating Pressure	2 Bar	
Signage	Drench Shower and Eyewash	
Certification	ANSI Z358.1 & AS 4775	


### \*Pipe Threads



# FULL STAINLESS STEEL FLOOR MOUNTED COMBINATION UNIT OF DRENCH SHOWER AND EYEWASH WITH FOOT PEDAL







# MODEL: ECB 10022 XSS | QCB 10022 XSS

This model is designed for cleanroom and areas where airborne particles is a concern. A non-coated fixture, it is the most durable unit of the emergency fixtures range.

Model	ECB 10022 XSS	QCB 10022 XSS
Stanchion	Stainless Steel 304 (Schedule 40)	Stainless Steel 316
Connecting Fittings	Stainless Steel 304 (Schedule 40)	Stainless Steel 316
Bowl Size	280	mm
Bowl Material	Stainless Steel	304 (Schedule 40)
Colour	Silver	gray
Connection Type	BS	SP
Outlet Size	1'	1
Inlet Size	1'	1
Shower Flow Rate	At least 90 lit	tres/ minute
Eyewash Flow Rate	At least 15 lit	res/ minute
Control Valve	Stainless	Steel 316
Operating Pressure	2 B	ar
Signage	Drench Showe	r and Eyewash
Certification	ANSI Z358.1	& AS 4775

#### \*Pipe Threads



### DECONTAMINATION SHOWER IN STAINLESS STEEL 304 PLATFORM OPERATED



### **MODEL: EPS SS-D150**

Our Decontamination Shower is popular in workplace where fire and chemical spillages may occur. All control valves are the instant action, stay opened type of ball valve. The unit also comes with a platform.

Model	EPS SS-D150
Stanchion	Stainless Steel 304
Connecting Fittings	Stainless Steel 304
Bowl Size	280mm
Bowl Material	Stainless Steel 304
Colour	Silver gray
Connection Type	BSP
Outlet Size	1"
Inlet Size	1"
Shower Flow Rate	At least 90 litres/ minute
Eyewash Flow Rate	At least 15 litres/ minute
Control Valve	Stainless Steel 316
Operating Pressure	2 Bar
Signage	Drench Shower
Certification	ANSI Z358.1 & AS 4775
Options	<ul> <li>EPS SS-D200 (Decontamination Eyewash in Stainless Steel 304)</li> <li>EPS SS-D300 (Decontamination Shower and Eyewash in Stainless Steel 304)</li> </ul>

#### \*Pipe Threads





# GRAVITY FED PORTABLE EYEWASH WITH WALL MOUNTING BRACKET





### MODEL: ES-ME6020

A durable self contained eyewash unit with an adjustable eyewash stream. Simple pull down to activate eyewash. Ideal for remote locations where access to continuous water supply is limited.

Model	ES-ME6020
Body	Food Grade High Density Polyethelene
Body Colour	Green
Flip Cover	Food Grade High Density Polyethelene
Flip Cover Colour	Yellow
Capacity	60 litres (16 gallons)
Activation	Pull Down
Eyewash Stream	Adjustable
Weight	6.2 kgs (Empty)
Size (L x W x H)	480 x 300 x 645 mm
Compliance	ANSI Z358.1 & AS 4775
Options	•ME 6001PRE  Uniquely formulated additive to protect bacterial and algae growth in self contained eyewash stations
	<b>ES-020ET</b> Durable and mobile transportation cart with discharge tank for self contained eyewash. Allows for easy relocation and draining

### \*Pipe Threads



# PORTABLE EYEWASH IN POLYETHYLENE C/W WALL BRACKET



### MODEL: ES-ME6008 | ES-ME6001

A durable self contained eyewash unit with an adjustable eyewash stream. Simple pull down to activate eyewash. Ideal for remote locations where access to continuous water supply is limited.

Model	ES-ME6008	ES-ME6001
Body	Food Grade High De	ensity Polyethelene
Body Colour	Yel	low
Capacity	30 litres (8 gallons)	60 litres (16 gallons)
Flow Speed (L/min)	2.6	2.6
Flushing Time (min)	9	18
Size (L x W x H)	342 x 350 x 625 mm	416 x 420 x 735 mm
Compliance	ANSI Z358.	1 & AS 4775
Options	<b>ES-060ET</b> Durable and mobile with discharge tank eyewash. Allows for and draining	for self contained

### PORTABLE EYEWASH MOBILE TROLLEY IN POLYETHYLENE



### **MODEL: ES-060ET**


Model	ES-060ET
Material	Polyethelene
Body Colour	Yellow
Capacity (Gal/I)	37.5/ 142
Size (L x W x H)	520 x 615 x 860 mm


#### \*Pipe Threads



#### STAINLESS STEEL PLATFORM WITH SUM AND REMOVABLE PERFORATED COVER







### **MODEL: ES PTS-100**

A suitable option when floors need to be kept as dry as possible. When used with the shower curtain system, it will contain water within sum of platform. A robust and durable platform with two easily removable cover for easy cleaning.


Model	ES PTS-100
Model	ES P13-100
Size (L x W x H)	1000 x 1000 x 150 mm
Material	Stainless Steel 304
Load Capacity	200 kgs
Drain Outlet	1 inch
Platform Cover	2 pieces removable
Compliance	ANSI Z358.1 & AS 4775
Recommendation	<ul> <li>ES SR-139         Stainless Steel Shower Rail without Curtain (Shower Mount)     </li> <li>ES SCW-18         Modesty Shower Curtain (Size: 1800 x 2000 mm) (2 pieces needed for ES SR-139)     </li> </ul>
Emergency Shower & Eyewash Fixture Quoted Separately (EBP Series)	<ul> <li>EBP 10020 AB         Combination Unit of Drench Shower &amp; Eyewash with ABS Plastic Bowl for ES PTS-100     </li> <li>EBP 10022 AB         Combination Unit of Drench Shower &amp; Eyewash with ABS Plastic Bowl &amp; Foot Pedal for ES PTS-100     </li> <li>EBP 10020 SS         Combination Unit of Drench Shower &amp; Eyewash with SS Bowl for ES PTS-100     </li> <li>EBP 10022 SS         Combination Unit of Drench Shower &amp; Eyewash with SS Bowl &amp; Foot Pedal for ES PTS-100     </li> </ul>

#### \*Pipe Threads



# BARRIER FREE FRP SHOWER BOOTH WITH ANTI SLIP GRATE





### **MODEL: ES FSE-100**

Fully assembled durable Fiber Reinforce Polyester Booth with IPS structure coplete with removable anti slip floor grate.

Model	ES FSE-100	
Booth Colour	White (Standard). Other colour upon request	
Booth Size (L x W x H)	1000 x 1000 x 2300 mm	
Shower Operation	Pull down the handle rod	
Eyewash Operation	Push the handle	
Waste	Floor Drain with cover	
Water Supply	1" IPS	
Pressure Requirement	30 PSI (2 Bar)	
Signage	Drench Shower and Eyewash	
Compliance	ANSI Z358.1	
Shower and Eyewash System	<ul> <li>EBT 100020SS         Combination Drench Shower with Stainless Steel Bowl and Eyewash without Bowl     </li> <li>EBT 100020AB         Combination Drench Shower with ABS Plastic Bowl and Eyewash without Bowl     </li> </ul>	

### \*Pipe Threads



# PORTABLE EMERGENCY SHOWER TANK TESTER



### **MODEL: ES011TT**

METHOD Emergency Shower Tank Tester has been developed to make maintenance of safety shower easier and quicker. Robustly designed and equipped with a holding tank and telescopic funnel, routine flushing can be done fuss free, eliminating spillages and handling of buckets.

Model	ES011TT
Dimension (W x D x H)	670 x 400 x 1820 mm
Structure	Steel sheet with epoxy powder baked
Unit Combine With	<ul> <li>100 litres transluscent tank with drain tap</li> <li>450mm diameter transluscent funnel</li> <li>Telescopic neck extension with teflon lock screw</li> <li>2 fixed wheels &amp; 2 lockable castors</li> </ul>





#### **MODEL: AVA-01**

Emergency audible and visual alarm, complete with flow switch.



#### MODEL: ES-SR-139

Stainless steel shower rail.

Size: 966mm Dia Material: SUS 304

Thickness: 1.2mm thick c/w support brace

- \* Shower curtain quoted separately
- \* 2 pieces of shower curtain required per unit shower rail



#### **MODEL: ES-SCG-18**

Light weight modesty shower curtain in light grey colour with plastic shower ring.

**Size:** 1800mm(L) x 2000mm(H)



### MODEL: ESPS-100-3/4

3/4" Stainless steel 316 scald protection valve for emergency shower and eyewash.



#### **MODEL: IVLP 55**

Eyewash assembly for low supply pressure. Suitable to be used for areas under 1 bar (15 psi) incoming pressure.

#### PARTS AND ACCESSORIES



IM 90-136

**ABS Plastic** Shower Bowl



IM 50-777

**ABS Plastic** Eyewash Bowl



S 09-200

Stainless Steel Shower Bowl



S 05-123

Stainless Steel Eyewash Bowl



**ES V10-1P** 

1" Stainless Steel 316 Control Ball Valve Only (Without Lever)



**ES E050** 

Stainless Steel Wire Braided Hose



**ES V05-1P** 

1/2" Stainless Steel 316 Control Ball Valve Only (Without Hand Push Plate)



IM 55-CD

Eyewash Head Assembly



S 128-2U

Stainless Steel Pull Rod



**IM 55-XSS** 

SS Eyewash Head Assembly



**ES-EE400** 

Drench Shower Tester Without Bucket (0.35mm UV Treated PVC Canvas)



IM 55-AV1X

ABS Eyewash Head Assembly with Tamper Proof Inbuilt Adjustable Flow Regulators



S 18-223

Stainless Steel Push Handle (ECB/EXG Series)



IM 26-166D

Foot Pedal with Stainless Steel Chain




0 25-069

6" SS Lever



#### ES-0020 | ES-0022

Product Signage & **Inspection Tag** 





ES E025-1FM

1''' Stainless Steel Flexible Hose C/w One End 1" Male Bspt SS 304 (Length: 12")





Scan here for official certification



# 500ml PLUM EYEWASH

**MODEL: EP 4604** 

Model	EP 4604
Description	A handy bottle with 0.9% sterile sodium chloride that can be used individually or as refill at eye wash stations and boxes. It comes with a dust cap.
Rinsing Time	About 5 minutes



# 200ml pH NEUTRAL EYEWASH

**MODEL: EP 4752** 

Model	EP 4752
Description	A small, handy pocket-size bottle with 4.9% sterile phosphate buffer that will quickly neutralize acids and alkali.
Rinsing Time	About 2 minutes





Scan here for official certification



# SINGLE PLUM WALL MOUNTED EYEWASH STATION

MODEL: EP 3000 + EP 4604

Model	EP 3000 + EP 4604
Description	Open wall station with single holder for 500ml PLUM Eyewash bottle.
Dimension (H x W xD)	291 x 114 x 2 mm
Content	1 x 500 ml Plum Eyewash (EP 4604) 1 x Wall Mounted Eyewash Station



### PLUM WALL MOUNTED EYEWASH STATION

MODEL: EP 4000 + EP 4604 (2 Nos)

Model	EP 4000 + EP 4604 (2 Nos)
Description	Open wall station with 2 holders for 500ml PLUM Eyewash bottles.
Dimension (H x W xD)	291 x 228 x 2 mm
Content	2 x 500 ml Plum Eyewash (EP 4604) 1 x Wall Mounted Eyewash Station





Scan here for official certification



# QUICKSAFE PLUM FIRST AID STATION

# EP 5170

Model	EP 5170			
Description	Fill the first aid station according to your needs. Eyewash for rinsing foreign bodies from the eye, pH Neutral for accidents with acids and alkali. Plasters and eyewah ampoules for minor accidents.			
Dimension (H x W xD)	430 x 253 x 92 mm			
Contents	2 x 500 ml Plum Eyewash 1 x 200 ml pH Neutral 5 x 20 ml QuickRinse Ampoules 1 x QuickFix Elastic Refill			





Scan here for official certification



# PLUM EYEWASH BOX

**MODEL: EP 4650** 

Model	EP 4650			
Description	Dust-proof wall station in impact-proof polystyrene which particularly suitable for production areas with a lot of dust, dirt, and for mobile workplaces.			
Dimension (H x W x D)	280 x 230 x 110 mm			
Content	2 x 500ml Plum Eyewash (EP 4604) 1x Dust-proof Wall Station			



# PLUM COMBI-BOX

**MODEL: EP 4787** 

Model	EP 4787			
Description	Dust-proof wall station in impact-proof polystyrene which particularly suitable for dusty production areas where there is a risk of accidents involving foreign bodies, acids and alkali.			
Dimension (H x W x D)	280 x 230 x 110 mm			
Content	1 x 200ml pH Neutral 1 x 500ml Plum Eyewash 1x Dust-proof Wall Station			



# PLUM QUICKFIX



Scan here for official certification

# QUICKFIX WATER RESISTANT

# EP 5501



Model	EP 5501		
Description	Wall mounted plaster dispenser that is suitable for working environment with a high level of humidity.  Dispenser: 135 x 230 x 32 mm  Refill: 72 x 25 mm		
Dimension (H x W x D)			
Content	2x 45 pieces of Water Resistant Plaster 1x wall mounted Plaster Dispenser		

# QUICKFIX WATER RESISTANT REFILL

### EP 5511



Model	EP 5511		
Description	Suitable for working environment with high level of humidity. The plaster are made of PE material, which allow the skin to breathe.		
Dimension (L x H)	72 x 25 mm		
Content	1x 45 pieces of Water Resistant Plaster		



NOTES			
	ı		





No 1, Jalan Pelubang 32/200, Persiaran Kemuning Prima, Seksyen 32, 40460 Shah Alam, Selangor, Malaysia

+603 5122 1818

+603 5131 7272

www.method.com.my



Photographs, drawings, logos and text on our commercial leaflets, on paper or digital, including our websites, registered or not with an intellectual property office are the exclusive property of Method \* Enterprise Sdn Bhd. Any intellectual property breach will lead to legal proceedings.

Copyright.
The content of this catalogue, on paper or digital, is the exclusive property of Method Enterprise Sdn Bhd. Any reproduction, editing and translating without consent is strictly prohibited.

Disclaimer:
No liabilities for printing errors, product alterations and model changes. Sizes and images may vary from actual product.